



US005908333A

United States Patent [19]

[11] Patent Number: 5,908,333

Perino et al.

[45] Date of Patent: Jun. 1, 1999

[54] CONNECTOR WITH INTEGRAL
TRANSMISSION LINE BUS

4,867,696	9/1989	Demler, Jr. et al.	174/72 B
5,104,324	4/1992	Grabbe et al.	439/62
5,329,424	7/1994	Patel	361/775

[75] Inventors: Donald Victor Perino, Los Altos;
James Anthony Gasbarro, Mountain
View; John Bradley Dillon, deceased,
late of Palo Alto, all of Calif., Nancy
David Dillon, legal representative

Primary Examiner—Neil Abrams

Attorney, Agent, or Firm—Blakely Sokoloff Taylor &
Zafman LLP

[73] Assignee: Rambus, Inc., Mt. View, Calif.

[21] Appl. No.: 08/897,788

[22] Filed: Jul. 21, 1997

[51] Int. Cl.⁶ H01R 9/09

[52] U.S. Cl. 439/631; 361/775; 174/72 B

[58] Field of Search 439/61, 631; 361/785,
361/775, 788; 172/71 B, 72 B, 88 B

[56] References Cited

U.S. PATENT DOCUMENTS

2,904,768	9/1959	Rasmussen	439/631
3,085,177	4/1963	Thompson	439/593
3,368,117	2/1968	Pond et al.	361/775
3,399,372	8/1968	Uberbacher	439/60
3,567,999	3/1971	Larson et al.	361/775
4,241,381	12/1980	Cobaugh et al.	439/61
4,536,826	8/1985	Ahiskali	361/775
4,616,893	10/1986	Feldman	439/83

[57] ABSTRACT

A socket (14) includes a first bus conductor (22a) having two or more contact regions (24) and a second bus conductor (22b) arranged substantially parallel to the first bus conductor and having two or more contact regions (24). The first and second bus conductors are spaced relative to one another so as to provide a predetermined electrical impedance and may be arranged to carry electrical signals as transmission lines. A dielectric spacer (36) may be disposed between the first and second bus conductors to provide the spacing. Contact regions (24) of the first and second conductors (22a, 22b) may provide compliant coupling regions for the socket (14). The contact regions (24) of the first bus conductor (22a) may be positioned within the socket (14) so as to contact a lead disposed on a first side of a circuit element (16) and the contact regions (24) of the second bus conductor (22b) may be positioned within the socket (14) so as to contact the lead disposed on the second side of the circuit element (16).

17 Claims, 11 Drawing Sheets

